

Model: AH6676D-B1O1BCN-8523

Description: H.265 2MP Outdoor IR IP Cam



SONY
STARVIS

Feature:

- H.265, H.264, MJPEG tri-encoder
- Up to 25 / 30 fps at all resolutions
- New Sony Starvis™ 1/2.8" sensor. The latest image sensor, Full color in low light
- Internal ICR , and long distance IR LED · Automatic day and night switch
- Network information security:802.1x, IP filter, HTTPS, RTC

Specification:

Camera	
Image Device	Sony 1/2.7" CMOS sensor , 2 mega-pixel image sensor
Effective pixels	1920x1080
Lens focal length	5-50mm lens, DC Iris
Min. Illumination	Color: 0.01 lux @F1.2 (AGC on) B/W: 0.005 lux @F1.2 (AGC on)
Day &Night	Mechanical ICR, Support 3 modes: Fully automatic switching, manual switching, external DI switching
IR LED	High power IR LED-light can be used day and night
Shutter	1/30-1/10,000s
WDR	Extreme WDR. Auto/Manual
Video	
Video Encoder	H.265, H.264 and MJPEG simultaneously
Video Profiles	Tri-encoder simultaneously 1920x1080, 1280x720, 640x480, 320x240
Frame Rate	Up to 25 / 30 fps at all resolutions
Exposure Control	Auto / Auto Indoor / Manual Exposure BLC Electronic Shutter Auto/Auto Indoor/Manual
Image Setting	AGC AE, AWB, Manual WB Control Automatic and manual shutter control 2D, 3D Noise reduction Color, brightness, sharpness, contrast, Hue Image Mirror/Flip, 90° Rotation
On Screen Display	Text, time and date overlay Multi-language OSD
Network	
Supported Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, SNMP, QoS, 802.1x
Network Package	Support Unicast and Multicast
Connection Security	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
Users	10 simultaneous unicast users
Ethernet	10M/100M auto detection
Alarm	
Alarm Triggers	Motion detection trigger, network disconnection trigger, camera image offset trigger, SD card un-mount unplugged trigger



聯發光電股份有限公司

Tel: +886-2-82269855

<https://www.a-mtk.com/en-us>

sales@a-mtk.com.tw

General	
Power Supply	110V AC in, or 12V DC in (Pls confirm your configuration to sales)
Working Temperature	-20°C to 60°C
WaterProof	IP66 for outdoor
Operating Humidity	20% ~ 80% (non-condensing)
Certificate	CE, FCC, RoHS
Viewing System	
OS	Windows® 7, 10
Browser	IE™, Chrome



Tel: +886-2-82269855
<https://www.a-mtk.com/en-us>
sales@a-mtk.com.tw